

(8182)63-90-72  
(7172)727-132  
(4722)40-23-64  
(4832)59-03-52  
(423)249-28-31  
(844)278-03-48  
(8172)26-41-59  
(473)204-51-73  
(343)384-55-89  
(4932)77-34-06  
(3412)26-03-58  
(843)206-01-48  
(4012)72-03-81  
(4842)92-23-67  
(3842)65-04-62  
(8332)68-02-04

(861)203-40-90  
(391)204-63-61  
(4712)77-13-04  
(4742)52-20-81  
(3519)55-03-13  
(495)268-04-70  
(8152)59-64-93  
(8552)20-53-41  
(831)429-08-12  
(3843)20-46-81  
(383)227-86-73  
(4862)44-53-42  
(3532)37-68-04  
(8412)22-31-16  
(342)205-81-47  
(863)308-18-15

:  
(4912)46-61-64  
(846)206-03-16  
- (812)309-46-40  
(845)249-38-78  
(4812)29-41-54  
(862)225-72-31  
(8652)20-65-13  
(4822)63-31-35  
(3822)98-41-53  
(4872)74-02-29  
(3452)66-21-18  
(8422)24-23-59  
(347)229-48-12  
(351)202-03-61  
(8202)49-02-64  
(4852)69-52-93

: wns@nt-rt.ru - : www.wsgenerator.nt-rt.ru

P11-6S



					50	60
/	:	3 /	:			
:		4-	:			
( )	/	84,0 (3,3)/90,0 (3,5)	3'	-	1,1 (38)	1,2 (43)
:				-	1,1 (38)	1,2 (43)
:				( . . )	3,0(12,0)	3,0(12,0)
:		ISO 8528				
:		22.5:1			50	60
:	( . . )	1,5 (91,3)	( )	:	5,3 (1,4)	5,3 (1,4)
:	/ 2( / 2)	2,17 (7415)		:		
/		12/	( ^ / )	-	11,6 (660)	13,6 (773)
		65		-	12,9 (734)	15,2 (864)
:	( ) -	197 (434)	( / )	-	4,9 (279)	6,0 (341)
		202 (445)		-	5,4 (307)	6,7 (381)
				:	0,2 (0,2)	0,3 (0,4)
				3' (^ . / )	28,8 (1017)	37,2(1314)
/	:	50 60		:	125 (0,5)	125 (0,5)
		1500 1800		( h2o)		
	( . )					50°C (122°F).
-		12,2(16,0)				14,7 (20,0)
-		13,5 (18,0)				16,2 (22,0)
:	( / . )	652,0 (94,6)		:		
-		722,0(104,7)	722,0(104,7)	( )		6,0 (1,6)
				:		4,5 (1,2)
				:		API CH4 15W-40
				:		N/A
:						
	/ ( / )				50	60
	110%	100%	75%	50%		
						Industrial
						263-0765 (1)
50	4,1 (1,1)	3,6 (1,0)	2,7 (0,7)	2,0 (0,5)		
60	4,8 (1,3)	4,3 (1,1)	3,3 (0,9)	2,4 (0,6)	( . . )	0,56(0,165) 0,80(0,236)
						30 18,6
	110%	100%	75%	50%	( Hg)	10,2 (3,0) 10,2 (3,0)
					3'	
50		4,1 (1,1)	2,9 (0,8)	2,1 (0,6)	-	2,7(95) 3,1(111)
60		4,8 (1,3)	3,5 (0,9)	2,6 (0,7)	-	2,9(102) 3,4(119)
(			0,85,			° (°f)
	BS2869, A2)				-	445 (833) 455 (851)
					-	490 (914) 505 (941)

	Leroy Somer	2250
	LLB1114F	+/- 1.0%
	1	NEMA = TIF: 100
	H	IEC = THF: 3.0%
	2/3 - M	LL/LN: 5.0%
	4	
	IP23	EN61000-6
		( / )
		- 50 1,9(108)
	R220	- 60 2,4(136)

		50		60
	240V	230V	220V	
				220V/110V 240V/120V
*	24	22	21	19 21
%	-	-	-	- -
Xd	1,410	1,530	1,670	2,410 2,030
X'd	0,240	0,260	0,290	0,420 0,350
X''d	0,122	0,132	0,145	0,208 0,175

\* 30% 0,9

		50		60
I	:	:	:	:
240V	10,0	10,0	11,0	11,0
230V	10,0	10,0	11,0	11,0
220V	10,0	10,0	11,0	11,0
			220V/110V	12,0 12,0 13,0 13,0
			240V/120V	12,0 12,0 13,0 13,0

(8182)63-90-72  
(7172)727-132  
(4722)40-23-64  
(4832)59-03-52  
(423)249-28-31  
(844)278-03-48  
(8172)26-41-59  
(473)204-51-73  
(343)384-55-89  
(4932)77-34-06  
(3412)26-03-58  
(843)206-01-48  
(4012)72-03-81  
(4842)92-23-67  
(3842)65-04-62  
(8332)68-02-04

(861)203-40-90  
(391)204-63-61  
(4712)77-13-04  
(4742)52-20-81  
(3519)55-03-13  
(495)268-04-70  
(8152)59-64-93  
(8552)20-53-41  
(831)429-08-12  
(3843)20-46-81  
(383)227-86-73  
(4862)44-53-42  
(3532)37-68-04  
(8412)22-31-16  
(342)205-81-47  
(863)308-18-15

:  
(4912)46-61-64  
(846)206-03-16  
- (812)309-46-40  
(845)249-38-78  
(4812)29-41-54  
(862)225-72-31  
(8652)20-65-13  
(4822)63-31-35  
(3822)98-41-53  
(4872)74-02-29  
(3452)66-21-18  
(8422)24-23-59  
(347)229-48-12  
(351)202-03-61  
(8202)49-02-64  
(4852)69-52-93

: wns@nt-rt.ru - : [www.wsngenerator.nt-rt.ru](http://www.wsngenerator.nt-rt.ru)