

(8182)63-90-72	(861)203-40-90	(4912)46-61-64
(7172)727-132	(391)204-63-61	(846)206-03-16
(4722)40-23-64	(4712)77-13-04	- (812)309-46-40
(4832)59-03-52	(4742)52-20-81	(845)249-38-78
(423)249-28-31	(3519)55-03-13	(4812)29-41-54
(844)278-03-48	(495)268-04-70	(862)225-72-31
(8172)26-41-59	(8152)59-64-93	(8652)20-65-13
(473)204-51-73	(8552)20-53-41	(4822)63-31-35
(343)384-55-89	(831)429-08-12	(3822)98-41-53
(4932)77-34-06	(3843)20-46-81	(4872)74-02-29
(3412)26-03-58	(383)227-86-73	(3452)66-21-18
(843)206-01-48	(4862)44-53-42	(8422)24-23-59
(4012)72-03-81	(3532)37-68-04	(347)229-48-12
(4842)92-23-67	(8412)22-31-16	(351)202-03-61
(3842)65-04-62	(342)205-81-47	(8202)49-02-64
(8332)68-02-04	- - (863)308-18-15	(4852)69-52-93

P110-3

P110-3

400V, 50	100,0	/ 80,0	110,0	/ 88,0	:	Perkins® 1104C-44TAG2
480V, 60	113,0	/ 90,4	125,0	/ 100,0	:	Marelli
					:	MJB 225 MA4
					:	DCP-10
					:	3-
					:	50 60
					:	1500 1800
1	12		10-		:	218 (57,6)
					:	
					:	21,7(5,7) 26,1 (6,9)
					:	23,9 (6,3) 29,0 (7,7)
8528-3).					:	ISO

25°C (77°F), 100 (328), 30%.

0,85 BS2869: 1998, A2.

-
-
-
-
-

1980 (78,0)	890 (35,0)	1317(51,9)	1115(2458)	1132(2496)
-------------	------------	------------	------------	------------

50 60

/	:	4 /	:			
:		4-	:			
()	/	105,0 (4,1)/127,0 (5,0)	2'	-	6,0 (212)	7,8 (274)
:				-	6,3 (221)	7,8 (275)
:				:	8,0 (32,1)	8,0 (32,1)
:						
:		ISO 8528 G2			50	60
:		18,3:1			17,5 (4,6)	17,5 (4,6)
:	(^ .)	4,4 (268,5)	()			
:	/ 2(/ 2)	1,51 (5160)				
:						
/		12/	(^ /)	-	46,1 (2622)	57,7(3281)
		65		-	50,7 (2883)	64,0 (3640)
:	() -	500 (1102)	(/)	-	13,9 (790)	17,2 (978)
		520 (1146)		-	16,2 (921)	19,3 (1098)
			:	(.)	2 8 (3 8)	4,8 (6,4)
			:	2' (. /)	187,8 (6632)	244,2 (8624)
/		50 60				
		1500 1800		(2)	125 (0,5)	125 (0,5)
						50°C (122°F).

-		93,6 (126,0)	106,8(143,0)			
-		103,0 (138,0)	117,5 (158,0)			
:	(/ .)	1702,0 (246,9)	1619,0 (234,8)			
-		1873,0 (271,7)	1781,0 (258,3)	()		(,)
				:		7,0 (1,8)
				:		API CC/SE

		Class A2 Diesel	BSEN590		50	60
	/ (/)					
	110%	100%	75%	50%	18,0 (5,3)	15,0 (4,4)
50	23,9 (6,3)	21,7 (5,7)	16,5 (4,4)	11,6 (3,1)	2'	
60	29,0 (7,7)	26,1 (6,9)	19,7(5,2)	14,1 (3,7)	-	15,2 (537)
					-	16,3 (576)
						20,4 (720)
		100%	75%	50%		° (°f)
					-	514 (957)
					-	517 (963)
50	23,9 (6,3)	18,0 (4,8)	12,6 (3,3)		-	543 (1009)
60	29,0(7,7)	21,6(5,7)	15,3(4,0)		-	574 (1065)

(BS2869, A2) 0,85,

	Marelli	/	2250
	MJB 225 MA4	()	+/- 1,0%
	1	NEMA = TIF:	50
	H	IEC = THF:	2,0%
	2/3 - M0	LL/LN:	2,0%
	12		EN55011
	IP23	(/)	
		- 50	8,7 (495)
	Mark V	- 60	9,9 (563)

		50				60			
		1							
	415/240V	400/230V	380/220V	220/127V	480/277V	380/220V	240/120V	440/254V	
		230/115V	220/110V		240/139V	220/110V	208/120V	220/127V	
		200/115V							
*	189	168	168	210	168	126	126	147	
%	-	-	-	-	-	-	-	-	
	Xd	2,430	2,620	2,900	2,160	2,470	2,860	3,290	2,930
	X'd	0,190	0,200	0,220	0,170	0,190	0,290	0,250	0,220
	X''d	0,088	0,094	0,104	0,078	0,089	0,138	0,119	0,106

* 30%- 0.

	50				60				
415/240V	100,0	80,0	110,0	88,0	480/277V	113,0	90,4	125,0	100,0
400/230V	100,0	80,0	110,0	88,0	220/127V	113,0	90,4	125,0	100,0
380/220V	100,0	80,0	110,0	88,0	380/220V	110,0	88,0	121,0	96,8
230/115V	100,0	80,0	110,0	88,0	240/120V	113,0	90,4	125,0	100,0
220/127V	100,0	80,0	110,0	88,0					
220/110V	100,0	80,0	110,0	88,0	440/254V	113,0	90,4	125,0	100,0
200/115V	100,0	80,0	110,0	88,0	220/110V	110,0	88,0	121,0	96,8
					208/120V	113,0	90,4	125,0	100,0
					240/139V	113,0	90,4	125,0	100,0

(8182)63-90-72
(7172)727-132
(4722)40-23-64
(4832)59-03-52
(423)249-28-31
(844)278-03-48
(8172)26-41-59
(473)204-51-73
(343)384-55-89
(4932)77-34-06
(3412)26-03-58
(843)206-01-48
(4012)72-03-81
(4842)92-23-67
(3842)65-04-62
(8332)68-02-04

(861)203-40-90
(391)204-63-61
(4712)77-13-04
(4742)52-20-81
(3519)55-03-13
(495)268-04-70
(8152)59-64-93
(8552)20-53-41
(831)429-08-12
(3843)20-46-81
(383)227-86-73
(4862)44-53-42
(3532)37-68-04
(8412)22-31-16
(342)205-81-47
(863)308-18-15

:
(4912)46-61-64
(846)206-03-16
- (812)309-46-40
(845)249-38-78
(4812)29-41-54
(862)225-72-31
(8652)20-65-13
(4822)63-31-35
(3822)98-41-53
(4872)74-02-29
(3452)66-21-18
(8422)24-23-59
(347)229-48-12
(351)202-03-61
(8202)49-02-64
(4852)69-52-93