

(8182)63-90-72  
(7172)727-132  
(4722)40-23-64  
(4832)59-03-52  
(423)249-28-31  
(844)278-03-48  
(8172)26-41-59  
(473)204-51-73  
(343)384-55-89  
(4932)77-34-06  
(3412)26-03-58  
(843)206-01-48  
(4012)72-03-81  
(4842)92-23-67  
(3842)65-04-62  
(8332)68-02-04

(861)203-40-90  
(391)204-63-61  
(4712)77-13-04  
(4742)52-20-81  
(3519)55-03-13  
(495)268-04-70  
(8152)59-64-93  
(8552)20-53-41  
(831)429-08-12  
(3843)20-46-81  
(383)227-86-73  
(4862)44-53-42  
(3532)37-68-04  
(8412)22-31-16  
(342)205-81-47  
(863)308-18-15

:  
(4912)46-61-64  
(846)206-03-16  
- (812)309-46-40  
(845)249-38-78  
(4812)29-41-54  
(862)225-72-31  
(8652)20-65-13  
(4822)63-31-35  
(3822)98-41-53  
(4872)74-02-29  
(3452)66-21-18  
(8422)24-23-59  
(347)229-48-12  
(351)202-03-61  
(8202)49-02-64  
(4852)69-52-93

P1700P1/P1875E1

# P1700P1/P1875E1

400V, 50 Hz      1700,0 / 1360,0      1875,0 / 1500,0  
 - / -      - / -  
 0,8

Perkins® 4012-46TAG3A  
 Leroy Somer  
 LL9224F  
 PowerWizard 1.1 +

1      12      10-  
 (      )  
 (      )  
 (      )  
 (      )  
 ISO  
 8528-3).

3-      50      60  
 1500  
 : /  
 (      )  
 ( 100- / )  
 (      ) -      351,5 (92,9)      -  
 -      392,6 (103,7)      -

25°C (77°F), 100 (328),      30%.  
 0,85      BS2869: 1998,      A2.

:  
 •  
 •  
 •  
 •  
 •

5101 (200,8)      2192 (86,3)      2453 (96,6)      11576 (25521)      11783 (25977)

ISO 8528, ISO 3046, IEC 60034, BS5000      NEMA  
 MG-1.22.

		12/Vee					
		4-		3 ( . / )			
( )	/	160,0 (6,3)/190,0 (7,5)				-	125,0 (4414)
						-	135,0 (4767)
							4,0 (16,1)
		ISO 8528 G2					
		13,6:1					50 60
		45,8 (2794,9)		( )			207,0 (54,7)
		19,30 (65951)					
		24/		( / )			510,0 (29003)
		40					625,0 (35543)
( )		4400 (9700)		( / )			171,4(9747)
		4604 (10150)					194,0 (11033)
							64,0 (85,8)
							1920,0 (67804)
		50 60					250 (1,0)
/		1500		( 2)			
		1500,0 (2012,0)					
		1643,0 (2203,0)					
( / )		2618,0 (379,7)					
		2868,0 (415,9)		( )			177,0 (46,8)
							159,0 (42,0)
							API CH4 15W-40
		Class A2 Diesel		BSEN590			
		110%		100%			50 60
		75%		50%			5,0 (1,5)
				( Hg)			
50	392,6 (103,7)	351,5 (92,9)	261,0 (68,9)	183,1 (48,4)	3 ^ ^ ^ )		350,0 (12360)
60	-	-	-	-			350,0 (12360)
		100%		75%			480 (896)
		50%					480 (896)
50	392,6 (103,7)	287,6 (76,0)	198,1 (52,3)				
60	-	-	-				
		0,85,					
(		BS2869, A2)					

Leroy Somer

: / 2250

LL9224F

( ) :

+ / 0,5%

1

NEMA = TIF:

50

H

IEC = THF:

2,0%

2/3 - 6 S

LL/LN:

3,5%

6

EN61006

IP23

: ( ^ / )

AREP

- 50

71,0(4038)

R449

- 60

-

50

60

415/240V

400/230V

380/220V

\* 4683

4364

3955

\*\* %

300

300

300

Xd

3,119

3,358

3,720

X'd

0,241

0,259

0,287

X''d

0,124

0,134

0,148

\* 30%-

0,4.

\*\*

50

60

415/240V

1700,0

1360,0

1875,0

1500,0

400/230V

1700,0

1360,0

1875,0

1500,0

380/220V

1700,0

1360,0

1875,0

1500,0

(8182)63-90-72  
(7172)727-132  
(4722)40-23-64  
(4832)59-03-52  
(423)249-28-31  
(844)278-03-48  
(8172)26-41-59  
(473)204-51-73  
(343)384-55-89  
(4932)77-34-06  
(3412)26-03-58  
(843)206-01-48  
(4012)72-03-81  
(4842)92-23-67  
(3842)65-04-62  
(8332)68-02-04

(861)203-40-90  
(391)204-63-61  
(4712)77-13-04  
(4742)52-20-81  
(3519)55-03-13  
(495)268-04-70  
(8152)59-64-93  
(8552)20-53-41  
(831)429-08-12  
(3843)20-46-81  
(383)227-86-73  
(4862)44-53-42  
(3532)37-68-04  
(8412)22-31-16  
(342)205-81-47  
(863)308-18-15

:  
(4912)46-61-64  
(846)206-03-16  
- (812)309-46-40  
(845)249-38-78  
(4812)29-41-54  
(862)225-72-31  
(8652)20-65-13  
(4822)63-31-35  
(3822)98-41-53  
(4872)74-02-29  
(3452)66-21-18  
(8422)24-23-59  
(347)229-48-12  
(351)202-03-61  
(8202)49-02-64  
(4852)69-52-93