

(8182)63-90-72
(7172)727-132
(4722)40-23-64
(4832)59-03-52
(423)249-28-31
(844)278-03-48
(8172)26-41-59
(473)204-51-73
(343)384-55-89
(4932)77-34-06
(3412)26-03-58
(843)206-01-48
(4012)72-03-81
(4842)92-23-67
(3842)65-04-62
(8332)68-02-04

(861)203-40-90
(391)204-63-61
(4712)77-13-04
(4742)52-20-81
(3519)55-03-13
(495)268-04-70
(8152)59-64-93
(8552)20-53-41
(831)429-08-12
(3843)20-46-81
(383)227-86-73
(4862)44-53-42
(3532)37-68-04
(8412)22-31-16
(342)205-81-47
(863)308-18-15

:
(4912)46-61-64
(846)206-03-16
- (812)309-46-40
(845)249-38-78
(4812)29-41-54
(862)225-72-31
(8652)20-65-13
(4822)63-31-35
(3822)98-41-53
(4872)74-02-29
(3452)66-21-18
(8422)24-23-59
(347)229-48-12
(351)202-03-61
(8202)49-02-64
(4852)69-52-93

: wns@nt-rt.ru - : www.wsgenerator.nt-rt.ru

P200-3

P200-3

| | | | | | | |
|-------------|-------|---|-------|-------|---|-------|
| 400V, 50 Hz | 180,0 | / | 144,0 | 200,0 | / | 160,0 |
| 480V, 60 Hz | 200,0 | / | 160,0 | 218,8 | / | 175,0 |

0,8

Perkins 1106A-70TAG3
Marelli
MJB 250 MB4
DCP-10

3-

50 60
1500 1800

394(104,1)

1

12

10-

(/)
(100- /)

39,8(10,5) 46,5 (12,3)
43,2(11,4) 50,6 (13,4)

8528-3).

ISO

25°C (77°F), 100 (328), 30%.
0,85 BS2869: 1998, A2.

-
-
-
-
-

(') (') (') () ' ()
2510(98,8) 1010 (39,8) 1640(64,6) 1552(3422) 1579 (3481)

L

ISO 8528, ISO 3046, IEC 60034, BS5000 NEMA

MG-1.22.

50 60

| | | | | | | |
|-----|-------------|-------------------------------|------------|------------|--------------------|---------------|
| / | : | 6 / | : | | | |
| : | | 4- | : | | | |
| () | / | 105,0 (4,1)/135,0 (5,3) | 3' (. /) | - | 13,1 (463) | 15,5 (546) |
| : | | | | - | 13,9 (490) | 16,4 (578) |
| : | | | (. .) | | 3,0 (12,0) | 3,0 (12,0) |
| : | | ISO 8528 G2 | | | 50 | 60 |
| : | | 16.0:1 | | | 27,0 (7,1) | 27,0 (7,1) |
| : | (.) | 7,0 (427,8) | () | | | |
| : | / 2(/ 2) | 1,26 (4306) | | | | |
| / | | 12/ | (/) | - | 74,2(4220) | 81,5 (4635) |
| | | 85 | | - | 76,4 (4345) | 88,3 (5022) |
| : | () - | 788 (1737) | (/) | | 22,2 (1262) | 30,3 (1723) |
| | | 822 (1812) | | - | 24,6 (1399) | 34,1 (1939) |
| | | | (.) | | 5,0 (6,7) | 10,0 (13,4) |
| | | | 3' (. /) | | 307,2 (10849) | 378,0 (13349) |
| / | | 50 60 | (H2O) | | 125 (0,5) | 125 (0,5) |
| | | 1500 1800 | | | | 50°C (122°F), |
| | | 167,6 (225,0) 180,5 (242,0) | | | | |
| | | 185,5 (249,0) 199,7(268,0) | | | | |
| : | (/ .) | 1912,0 (277,3) 1715,0 (248,8) | | | | |
| | | 2116,0 (306,9) 1898,0 (275,3) | () | | 16,5 (4,4) | |
| | | | () | | 14,9 (3,9) | |
| | | | | | API CH4/C14 15W-40 | |
| | | Class A2 Diesel BSEN590 | | | | |
| | (/) | | | | 50 | 60 |
| | 110% | 100% | 75% | 50% | 6,0 (1,8) | 6,0 (1,8) |
| | | | | (Hg) | | |
| 50 | 43,2(11,4) | 39,8(10,5) | 30,7(8,1) | 19,6 (5,2) | 31,6 (1114) | 35,4 (1251) |
| 60 | 50,6(13,4) | 46,5 (12,3) | 35,4 (9,4) | 23,6 (6,2) | 33,9 (1195) | 38,4 (1354) |
| | | 100% | 75% | 50% | | |
| | | | | | °C(°F) | |
| 50 | 43,2(11,4) | 33,9 (9,0) | 22,2 (5,9) | | 538 (1000) | 485 (905) |
| 60 | 50,6 (13,4) | 38,6 (10,2) | 26,0 (6,9) | | 538 (1000) | 485 (905) |

(BS2869, A2) 0,85,

Leroy Somer

MJB 250 MB4

1

H

2/3 - M0

12

IP23

Mark V

2250

+/- 0.5%

NEMA = TIF:

50

IEC = THF:

2.0%

LL/LN:

2.0%

EN61000-6

- 50 12,2 (694)

- 60 14,6 (830)

50

1

60

| | 415/240V | 400/230V | 380/220V | 220/127V | 480/277V | 380/220V | 240/120V | 440/254V |
|--|----------|----------|----------|----------|----------|----------|----------|----------|
| | | 230/115V | 220/110V | | 240/139V | 220/110V | 208/120V | 220/127V |
| | | 200/115V | | | | | | |

* 260 241 217 291 237 170 194 212

% - - - - - - - -

| | | | | | | | | |
|-----|-------|-------|-------|-------|-------|-------|-------|-------|
| Xd | 3,040 | 3,270 | 3,620 | 2,700 | 3,020 | 4,716 | 4,034 | 3,617 |
| X'd | 0,260 | 0,280 | 0,310 | 0,230 | 0,259 | 0,402 | 0,343 | 0,308 |
| X"d | 0,104 | 0,112 | 0,124 | 0,092 | 0,104 | 0,161 | 0,138 | 0,123 |

* 30%- 0,6.

50

60

| | | | | | | | | | |
|----------|-------|-------|-------|-------|----------|-------|-------|-------|-------|
| 415/240V | 180,0 | 144,0 | 200,0 | 160,0 | 480/277V | 200,0 | 160,0 | 218,8 | 175,0 |
| 400/230V | 180,0 | 144,0 | 200,0 | 160,0 | 220/127V | 200,0 | 160,0 | 218,8 | 175,0 |
| 380/220V | 180,0 | 144,0 | 200,0 | 160,0 | 380/220V | 195,0 | 156,0 | 215,0 | 172,0 |
| 230/115V | 180,0 | 144,0 | 200,0 | 160,0 | 240/120V | 199,5 | 159,6 | 218,8 | 175,0 |
| 220/127V | 180,0 | 144,0 | 200,0 | 160,0 | | | | | |
| 220/110V | 180,0 | 144,0 | 200,0 | 160,0 | 440/254V | 200,0 | 160,0 | 218,8 | 175,0 |
| 200/115V | 180,0 | 144,0 | 200,0 | 160,0 | 220/110V | 195,0 | 156,0 | 215,0 | 172,0 |
| | | | | | 208/120V | 199,5 | 159,6 | 218,8 | 175,0 |
| | | | | | 240/139V | 200,0 | 160,0 | 218,8 | 175,0 |

(8182)63-90-72
(7172)727-132
(4722)40-23-64
(4832)59-03-52
(423)249-28-31
(844)278-03-48
(8172)26-41-59
(473)204-51-73
(343)384-55-89
(4932)77-34-06
(3412)26-03-58
(843)206-01-48
(4012)72-03-81
(4842)92-23-67
(3842)65-04-62
(8332)68-02-04

(861)203-40-90
(391)204-63-61
(4712)77-13-04
(4742)52-20-81
(3519)55-03-13
(495)268-04-70
(8152)59-64-93
(8552)20-53-41
(831)429-08-12
(3843)20-46-81
(383)227-86-73
(4862)44-53-42
(3532)37-68-04
(8412)22-31-16
(342)205-81-47
(863)308-18-15

:
(4912)46-61-64
(846)206-03-16
- (812)309-46-40
(845)249-38-78
(4812)29-41-54
(862)225-72-31
(8652)20-65-13
(4822)63-31-35
(3822)98-41-53
(4872)74-02-29
(3452)66-21-18
(8422)24-23-59
(347)229-48-12
(351)202-03-61
(8202)49-02-64
(4852)69-52-93

: wns@nt-rt.ru - : www.wsngenerator.nt-rt.ru