

(8182)63-90-72
(7172)727-132
(4722)40-23-64
(4832)59-03-52
(423)249-28-31
(844)278-03-48
(8172)26-41-59
(473)204-51-73
(343)384-55-89
(4932)77-34-06
(3412)26-03-58
(843)206-01-48
(4012)72-03-81
(4842)92-23-67
(3842)65-04-62
(8332)68-02-04

(861)203-40-90
(391)204-63-61
(4712)77-13-04
(4742)52-20-81
(3519)55-03-13
(495)268-04-70
(8152)59-64-93
(8552)20-53-41
(831)429-08-12
(3843)20-46-81
(383)227-86-73
(4862)44-53-42
(3532)37-68-04
(8412)22-31-16
(342)205-81-47
(863)308-18-15

:
(4912)46-61-64
(846)206-03-16
- (812)309-46-40
(845)249-38-78
(4812)29-41-54
(862)225-72-31
(8652)20-65-13
(4822)63-31-35
(3822)98-41-53
(4872)74-02-29
(3452)66-21-18
(8422)24-23-59
(347)229-48-12
(351)202-03-61
(8202)49-02-64
(4852)69-52-93

: wns@nt-rt.ru

P500-1

P500-1

400V, 50 Hz 455,0 / 364,0 500,0 / 400,0 Perkins® 2506A-E15TAG1
 - / - - / - Leroy Somer
 0,8 PowerWizard 1.1 +

1 12 10- 3- 50 60
 () 1500 -
 () 888 (234,6)
 () (100- /) 94,0 (24,8) -
 - - 103,1 (27,2) -

8528-3). () ISO

25°C (77°F), 100 (328), 30%.
 0,85 BS2869: 1998, A2.

3800 (149,6) 1131 (44,5) 2215 (87,2) 3676 (8104) 3734 (8232)

MG-1.22. ISO 8528, ISO 3046, IEC 60034, BS5000 NEMA

50 60

/ : 6 / :
 : 4- :
 () / : 137,0 (5,4)/171,0 (6,7) 2 - 25,8(911) -
 : - 30,5 (1077) -
 : (. .) 6,2 (24,9) -

: ISO 8528 G2
 : 16,0:1 50 60
 : (^ .) 15,2 (927,6) () : 58,1 (15,3) -
 : / 2(/ 2) 4,29 (14660) :

/ 24/ (^ /) : 134,0 (7620) -
 70 - 147,0 (8360) -

: () - 1633 (3600) , (/) :
 - 1714 (3779) - 51,1 (2906)
 - 59,0 (3355)
 : (.) 13,7(18,4) -

50 60 : 2 (^ . /) 476,4 (16824) -
 / : 1500 - : (2) 125 (0,5) -
 : (.) 50°C (122°F).

- 412,0 (553,0)
 - 451,0 (605,0)

: (/ .) 2235,0 (316,1)
 2447,0 (346,0) () : 62,0 (16,4)
 : () : 53,0 (14,0)
 : API CI4 15W-40

: A2
 , / (/) 50 60
 110% 100% 75% 50% : 6,8 (2,0) -
 (H)

50 103,1 (27,2) 94,0 (24,8) 71,8(19,0) 51,2(13,5) 3 :
 60 - - - - - 71,4 (2521) -
 - - - - - 81,0 (2860) -

: ° (°f)
 100% 75% 50% - 500 (932)
 50 103,1 (27,2) 78,3 (20,7) 55,2(14,6) - 550 (1022)
 60

	Leroy Somer	2250
	LL6114D	+/- 0.5%
	1	NEMA = TIF: 50
	H	IEC = THF: 2.0%
	2/3-6	LL/LN: 4.0%
	12	EN61000-6
	IP23	
		(/)
		-50 27,8(1581)
		-60 -

	50	60	
	415/240V	400/230V	380/220V

* 987 923 840

** % 300 300 300

Xd	3,320	3,570	3,950
X'd	0,180	0,190	0,210
X''d	0,125	0,135	0,149

* 30%- 0,6

50	60
:	:

415/240V	455,0	364,0	500,0	400,0
400/230V	455,0	364,0	500,0	400,0
380/220V	455,0	364,0	500,0	400,0

:

(8182)63-90-72
(7172)727-132
(4722)40-23-64
(4832)59-03-52
(423)249-28-31
(844)278-03-48
(8172)26-41-59
(473)204-51-73
(343)384-55-89
(4932)77-34-06
(3412)26-03-58
(843)206-01-48
(4012)72-03-81
(4842)92-23-67
(3842)65-04-62
(8332)68-02-04

(861)203-40-90
(391)204-63-61
(4712)77-13-04
(4742)52-20-81
(3519)55-03-13
(495)268-04-70
(8152)59-64-93
(8552)20-53-41
(831)429-08-12
(3843)20-46-81
(383)227-86-73
(4862)44-53-42
(3532)37-68-04
(8412)22-31-16
(342)205-81-47
(863)308-18-15

(4912)46-61-64
(846)206-03-16
- (812)309-46-40
(845)249-38-78
(4812)29-41-54
(862)225-72-31
(8652)20-65-13
(4822)63-31-35
(3822)98-41-53
(4872)74-02-29
(3452)66-21-18
(8422)24-23-59
(347)229-48-12
(351)202-03-61
(8202)49-02-64
(4852)69-52-93

: wns@nt-rt.ru