

(8182)63-90-72
(7172)727-132
(4722)40-23-64
(4832)59-03-52
(423)249-28-31
(844)278-03-48
(8172)26-41-59
(473)204-51-73
(343)384-55-89
(4932)77-34-06
(3412)26-03-58
(843)206-01-48
(4012)72-03-81
(4842)92-23-67
(3842)65-04-62
(8332)68-02-04

(861)203-40-90
(391)204-63-61
(4712)77-13-04
(4742)52-20-81
(3519)55-03-13
(495)268-04-70
(8152)59-64-93
(8552)20-53-41
(831)429-08-12
(3843)20-46-81
(383)227-86-73
(4862)44-53-42
(3532)37-68-04
(8412)22-31-16
(342)205-81-47
(863)308-18-15

:
(4912)46-61-64
(846)206-03-16
- (812)309-46-40
(845)249-38-78
(4812)29-41-54
(862)225-72-31
(8652)20-65-13
(4822)63-31-35
(3822)98-41-53
(4872)74-02-29
(3452)66-21-18
(8422)24-23-59
(347)229-48-12
(351)202-03-61
(8202)49-02-64
(4852)69-52-93

: wns@nt-rt.ru - : www.wsngenerator.nt-rt.ru

P550-3

P550-3

400V, 50 Hz 500,0 / 400,0 550,0 / 440,0
 - / - - / -
 0,8

Perkins 2506A-E15TAG2
 EG315L-400N
 PowerWizard 1.1 +

1 12 10- 50 60
 () 1500 -
 () 888 (234,6)
 (100- /) 97,2 (25,7) -
 () 107,4(28,4) -

8528-3). () ISO
 25°C (77°F), 100 (328), 30%.
 0,85 BS2869: 1998, A2.

-
-
-
-
-

(') (') (') (') (')
 3800 (149,6) 1131 (44,5) 2215 (87,2) 3641 (8027) 3699 (8155)

= =
 ISO 8528, ISO 3046, IEC 60034, BS5000 NEMA
 MG-1.22.

/	:	6 /	:			
:		4-	:			
()	/	137,0 (5,4)/171,0 (6,7)	3' (. /)	-	35,8 (1264)	
				-	36,6 (1293)	-
			(. .)		6,2 (24,9)	
		ISO 8528 G2			50	60
		16,0:1			58,1 (15,3)	-
	(.)	15,2 (927,6)	()			
	/ 2(/ 2)	4,29 (14660)				
		24/	(/)	-	147,0 (8360)	
		70		-	165,0 (9383)	
	() -	1633 (3600)	(/)	-	54,3 (3088)	
		1714 (3779)		-	62,5 (3554)	
			(.)		13,7 (18,4)	
			3' (. /)		476,4 (16824)	
		50 60			125 (0,5)	
/		1500	(H2O)			
	(.)					50°C (122°F)
	-	451,0 (605,0)				
	-	495,0 (664,0)				
	(/ .)	2405,0 (346,0)				
	-	2640,0 (379,8)	()		62,0 (16,4)	
			()		53,0 (14,0)	
					API CI4 15W-40	
		Class A2 Diesel	BSEN590			
	/ (/)				50	60
	110%	100%	75%	50%	6,8 (2,0)	-
					(H)	
50	107,4 (28,4)	97,2 (25,7)	73,6 (19,4)	52,8 (13,9)	3' (. /)	
60	-	-	-	-		94,0 (3320)
						98,0 (3461)
		100%	75%	50%		°C(°F)
						500 (932)
50	107,4 (28,4)	80,3 (21,2)	56,9 (15,0)			550 (1022)
60	-	-	-			
(BS2869, A2)	0,85,			

					2250
		EG315L-400N			+/-1%
		1		NEMA = TIF:	50
		H		IEC = THF:	2,0%
		2/3 - R1		LL/LN:	3,0%
		12			
		IP21			
		EVC600i			
				- 50	27,5 (1564)
				- 60	

			50		60
		415/240V	400/230V	380/220V	

			230 V	
*		1115	1030	950
** %		300	300	300
	Xd	3,317	3,571	3,759
	X'd	0,122	0,131	0,138
	X''d	0,110	0,118	0,124

* 30%-
 ** 0,4 SHUNT.

		50		60
--	--	----	--	----

			I		I
415/240V	500,0	400,0	550,0	440,0	
400/230V	500,0	400,0	550,0	440,0	
380/220V	475,0	380,0	546,3	437,0	
230 V	500,0	400,0	550,0	440,0	

(8182)63-90-72
(7172)727-132
(4722)40-23-64
(4832)59-03-52
(423)249-28-31
(844)278-03-48
(8172)26-41-59
(473)204-51-73
(343)384-55-89
(4932)77-34-06
(3412)26-03-58
(843)206-01-48
(4012)72-03-81
(4842)92-23-67
(3842)65-04-62
(8332)68-02-04

(861)203-40-90
(391)204-63-61
(4712)77-13-04
(4742)52-20-81
(3519)55-03-13
(495)268-04-70
(8152)59-64-93
(8552)20-53-41
(831)429-08-12
(3843)20-46-81
(383)227-86-73
(4862)44-53-42
(3532)37-68-04
(8412)22-31-16
(342)205-81-47
(863)308-18-15

:
(4912)46-61-64
(846)206-03-16
- (812)309-46-40
(845)249-38-78
(4812)29-41-54
(862)225-72-31
(8652)20-65-13
(4822)63-31-35
(3822)98-41-53
(4872)74-02-29
(3452)66-21-18
(8422)24-23-59
(347)229-48-12
(351)202-03-61
(8202)49-02-64
(4852)69-52-93

: wns@nt-rt.ru - : www.wsngenerator.nt-rt.ru